# 





# ECOMAT PLUS

Economical semi-automatic Ecomat wrapping machines are reliable, safe and easy to use.



## **Efficiency**

- Motorized Power Pre Stretch System (260%)
- Stepless film-tension control
- All types of power pre-stretch films can be used (i.e. Mima Films UP, BH)
- Minimum consumption of film per pallet
- Optimisation of cost per pallet

# Safety

- Film carriage inside the tower
- Safe, fast and ergonomic film loading
- Control for door opening
- Emergency stop



# **Simplicity**

- Fast and simple installation
- Safe transportation (machine) packed in a wooden crate)
- Easy maintenance
- Height sensoring by photocell (wrapping of black goods also possible)
- Easy film feeding the film is just placed in the middle of the carriage and threaded through the threading slot



## Easy to use

- Adjustable number of top and bottom wraps
- Adjustable carriage and turntable speed
- Support layer function
- Soft START/STOP
- Indexed stop
- 15 easily adjustable memorizable programs
- Adjustable "over the pallet" wrapping



## **Ontions**

- Access ramp
- Pit foundation template
- Load stabilizer
- Turntable diameter 2 m



# **Technical data**

Capacity

Power supply Turntable speed Turntable height Film carriage Machine dimensions:

Turntable Ø: Space required: Machine weight: Wrapping height: Max. pallet weight:

Pallet dimensions:

15 - 25 pallets/h (depending on pallet dimensions)

220-240V/50Hz

2-12 rpm 80 mm

1650 mm

variable climbing speed 2575 x 1650 mm

4.3 m<sup>2</sup> (height 2900 mm) approx. 430 kg 2400 mm

2000 kg (1200 kg for FS option model) L =1200 mm, W=1200 mm, H=2400 mm

